

ENGINE COOLANT

Supacool Engine Coolant and Rust Inhibitor **Supacool**





SUPACOOL

Description

SupaCool is a specially formulated based on ethylene glycol oil free anti-corrosion additive for the cooling system of all types of vehicles and stationary combustion engines operated in frost free climates. It has low silicate concentrations and contains corrosion inhibitors based on organic and inorganic acids and non-ferrous metal deactivators making it suitable for use in aluminium radiators of most OEMs.

Applications

SupaCool is pre-diluted with 50% of de-ionised water making it readily suitable for use both in automotive and industrial heavy duty equipment where an anti-free or coolant is required to provide protection against freezing, boil-over and corrosion.

Benefits

- Excellent heat transfer properties
- Excellent anti-foam properties
- Low silicate content
- Ready to use pre-diluted product

Performance

ASTM D3306 for automotive service | ASTM D4985 for heavy duty diesel service |IS K2234

SUPACOOL CIC

Description

SupaCool CIC is a specially formulated aqueous concentrate water treatment agent of specific organic corrosion and cavitation inhibitors, and contains absolutely no phosphate, nitrites, amines, boron, nitrates or silicates ensuring it is non-polluting and long lasting.

Applications

SupaCool CIC at 5 to 10% concentration in soft water (hardness below 20° TH, no zinc and 300 ppm maximum chlorides and sulphates) will protect cooling systems in diesel and gas engines in power plants, heat plants and ships requiring no anti-freeze protection. Above 5% concentration should be used in flushing circuits and 10% concentration for stationary engines, engines on test or long storage.

Benefits

- Excellent corrosion and cavitation protection
- Clean and deposit free cooling circuits
- Suitable for domestic heating systems as it is non-polluting
- High thermal capacity at lower cost

Performance

MAN | MTU | WARTSILA | GE



ENERGIZING KENYA

KAWI Complex, Popo Lane, Off Red Cross Road, South C, Nairobi Kenya. P.O. Box 58567, 00200 Nairobi, Kenya

Telephone: +254-20-6952000 | Mobile: 0734-333000 / 0722 203 748 / 0726 610 102

Email: ceo@nockenya.co.ke | Website: www.nationaloil.co.ke