





SUPADEO SERIES CF 30, 40

Description

SupaDEO Series are premium quality cylinder and crankcase oils specially formulated for use in high output medium speed trunk-piston marine diesel engines which are designed to operate on heavy residual fuel with sulphur content between 2.0% to 3.5% by weight operating under severe work load.

Applications

SupaDEO Series oils are highly recommended for the lubrication of medium speed trunk piston engine burning high sulphur residual fuels in which excellent engine cleanliness is required by system and engine operational condition in order to overcome the "black sludge" and its associated problems. Selection of oil grade depends on the level of sulphur present by weight in the residual fuel as follows;

- L30 for engine burning light to heavy residual fuel with sulphur content of 2.0% to 2.5%
- L40 for engine burning light to heavy residual fuel, sulphur content of 2.0% to 2.5%
- M40 for engine fitted with anti-polishing ring burning heavy residual fuel with sulphur content of up to 3.0%
- H40 for engine fitted with anti-polishing ring burning heavy residual fuel with sulphur content of up to 3.5%

Benefits

- Advanced detergent and dispersant additive technology for excellent engine cleanliness
- Excellent high temperature oxidation and thermal stability
- Exceptional high level of wear and corrosion protection even with high sulphur fuels

Performance

API CF | Wartsila | MAN Diesel | Caterpillar Micro Oxidation Test Performance | Heavy Fuel Caterpillar IMPC





ENERGIZING KENYA

KAWI Complex, Popo Lane, Off Red Cross Road, South C, Nairobi Kenya. P.O. Box 58567, 00200 Nairobi, Kenya

Telephone: +254-20-6952000 | Mobile: 0734-333000 / 0722 203 748 / 0726 610 102

Email: ceo@nockenya.co.ke | Website: www.nationaloil.co.ke